

## Tubular

### STW 2V TUBULAR WET BATTERIES

(in accordance to DIN standards)



Model	Nominal Voltage	Capacity		Dimensions LxWxH mm	Weight (kg)	
		C10	C100		empty	full
STW 290	2	213	290	105 x 208 x 420	17.2	22.1
STW 365	2	266	365	126 x 208 x 420	20.8	27.5
STW 440	2	320	440	147 x 208 x 420	24.3	31.5
STW 520	2	390	520	126 x 208 x 525	26.9	34.8
STW 625	2	468	625	147 x 208 x 525	31.5	40.9
STW 730	2	546	730	168 x 208 x 525	36.1	47
STW 890	2	686	890	147 x 208 x 710	44.8	57.7
STW 1190	2	915	1190	215 x 193 x 710	61.3	78.2
STW 1490	2	1143	1490	215 x 235 x 710	74.6	95.7
STW 1785	2	1372	1785	215 x 277 x 710	88	113.5
STW 2230	2	1609	2230	215 x 277 x 855	114.3	148.5
STW 2980	2	2146	2980	215 x 400 x 815	151.5	199.5
STW 3725	2	2682	3725	215 x 490 x 815	193	261
STW 4470	2	3219	4470	215 x 580 x 815	246	322

### STW (large) 2V TUBULAR WET BATTERIES

(in accordance to DIN standards)



Model	Nominal Voltage	Capacity		Dimensions LxWxH mm	Weight (kg)	
		C10	C100		empty	full
STW 4900	2	3780	4914	440 x 422 x 885	359	451
STW 5600	2	4320	5616	440 x 466 x 885	378	482
STW 6300	2	4860	6318	440 x 510 x 885	440	555
STW 7020	2	5400	7020	440 x 568 x 885	470	597
STW 7700	2	5940	7722	440 x 612 x 885	530	668
STW 8400	2	6480	8424	440 x 656 x 885	565	722
STW 9800	2	7560	9828	440 x 890 x 885	710	924
STW 11200	2	8640	11232	440 x 890 x 885	755	965
STW 12600	2	9720	12636	440 x 1090 x 885	890	1153
STW 14000	2	10800	14040	440 x 1090 x 885	935	1195
STW 15400	2	11880	15444	440 x 1266 x 885	1060	1369
STW 16800	2	12960	16848	440 x 1266 x 885	1110	1416

### STW (non DIN) 2V TUBULAR WET BATTERIES



Model	Nominal Voltage	Capacity		Dimensions LxWxH mm	Weight (kg)	
		C10	C100		empty	full
STW 375	2	250	375	198 x 64.5 x 747	19.3	25.7
STW 560	2	375	560	198 x 82.5 x 747	26.4	34.7
STW 750	2	500	750	198 x 100.5 x 747	33.4	43.6
STW 935	2	625	935	198 x 118.5 x 747	40.3	52.1
STW 1125	2	750	1125	198 x 136.5 x 747	47.4	61
STW 1310	2	875	1310	198 x 172.5 x 747	56.9	74.7
STW 1500	2	1000	1500	198 x 190.5 x 747	64.2	83.9

### STW (block) 6V/12V TUBULAR WET BATTERY BLOCS

(in accordance to DIN standards)



Model	Nominal Voltage	Capacity		Dimensions LxWxH mm	Weight (kg)	
		C10	C100		empty	full
STW 70-12	12	50	70	272 x 205 x 383	37	52
STW 140-12	12	100	140	272 x 205 x 383	48	61
STW 210-12	12	150	210	380 x 205 x 383	67	85
STW 280	6	200	280	272 x 205 x 383	47	60
STW 350	6	250	350	380 x 205 x 383	60	80
STW 420	6	300	420	380 x 205 x 383	67	85

### STG (bloc) 6V/12V TUBULAR GEL BATTERY BLOCS

(in accordance to DIN standards)




Model	Nominal Voltage	Capacity		Dimensions LxWxH mm	Weight (kg)
		C10	C100		
STG60-12	12	50	60	272 x 205 x 383	38
STG120-12	12	100	120	272 x 205 x 383	52
STG180-12	12	150	180	380 x 205 x 383	74
STG240	6	200	240	272 x 205 x 383	51
STG300	6	250	300	380 x 205 x 383	66

### STG 2V TUBULAR GEL BATTERIES

(in accordance to DIN standards)



Model	Nominal Voltage	Capacity		Dimensions LxWxH mm	Weight (kg)
		C10	C100		
STG 270	2	230	270	105 x 208 x 420	20
STG 340	2	290	340	126 x 208 x 420	24
STG 410	2	350	410	147 x 208 x 420	28
STG 470	2	360	470	126 x 208 x 525	31
STG 570	2	430	570	147 x 208 x 525	37
STG 660	2	510	660	168 x 208 x 525	42
STG 810	2	600	810	147 x 208 x 710	50
STG 1080	2	800	1080	215 x 193 x 710	68
STG 1350	2	1000	1350	215 x 235 x 710	82
STG 1620	2	1200	1620	215 x 277 x 710	97
STG 2030	2	1500	2030	215 x 277 x 855	120
STG 2700	2	2000	2700	215 x 400 x 815	165
STG 3380	2	2500	3380	215 x 490 x 815	200
STG 4060	2	3000	4060	215 x 580 x 815	240



Figures given for height include battery terminals