

SOLLATEK AUTOMATIC VOLTAGE REGULATOR (AVR)

Single phase wide input telecom static AVR

Model:

AVR23-22-TT
Single phase: 5kVA

Features:

Designed for telecom applications
Designed for regions with severe low voltage supply
Designed for remote operation where a high degree of reliability is essential

Fully electronic with no moving parts for:

- High reliability
- Speed of operation
- Immunity to dust and other environmental conditions

The AVR is specified and used by a number of large organisations including:

- Satellite operators
- Infrastructure telecom companies
- Embassies worldwide for reliable electrification of their posts
- Medical systems for digital imaging, scanning and x-ray equipment
- Mobile phone operators
- Grid utility companies for voltage regulation to their sub-stations
- Various United Nations divisions including WHO, UNICEF and WFP

Equipped with:

- Digital display: input and output voltage, input and output current, frequency
- Low and high voltage protection
- Radio frequency interference filtering
- Audible and visual alarm

Special features include:

- Wide input frequency tolerance between 45 to 75 Hz allowing unit to function properly in areas of severe voltage disturbances
- High overload capability with up to 150% for 4 minutes
- Very low losses and minimal heat dissipation due to an efficiency of over 96% at full load
- Warranty of 2 years. Sollatek provides full back up support on all its products, with local support in over twenty countries worldwide



AVR23

Specifications

Input

Input voltage	220V, -50%, +20%.
Maximum Input Current	44 amps (at 100% load and maximum boost).
Frequency range	45Hz to 75Hz (i.e 50Hz -10%, +50%. or 60Hz -25%, +25%).
Additional Voltage THD	<0.2% at input (tested at 100% linear load), (No PWM methods used).
Maximum Input THD	Can withstand >10% THD from the supply.


Output

Output voltage	220V, +/- 4%.
Maximum Output Current	23 amps.
Maximum Output Power	5 kVA.
Correction time	40 m sec (0 to 100% load).
Additional Voltage THD	<0.25% at output (tested at 100% linear load), (No PWM methods used).
Crest Factor	> 1:3 permissible on load current (tested at 100% load).
Synchronization	Output synchronized to input.
Permissible Overload	1000% for 100ms, 150% for 4 minutes, 110% for 10 minutes.
Load Types	Designed to run lighting, motors, battery chargers, communications equipment, office equipment, SMPS, air- conditioners, compressors, industrial machines, medical equipment and others. Suitable for all domestic, commercial and industrial sites.

Control Aux Unit CAU (N.B. The following items are mounted in a single separate wall box from the AVR for convenient operation)

CAU type	CAU1-50-2.
Circuit Breakers	Input and output circuit breakers to protect against overload and short circuit to both the AVR and the load.
Voltage Protection	AVS Automatic over and under voltage protection and re-connect delay, c/w five status LED indicators. Protects load from extreme supply voltage and AVR malfunction.
Output Alarm	Visual indicator, audible alarm and volt-free contacts if AVR output fails for any reason. Mute button provided for audible alarm.

General

Technology	All solid state (static) switching.
Efficiency	>96% (at 100% linear load).
Control	Microcontroller based control system provides self checks, system integrity monitoring and diagnostic indicators.
Control Protection	Internal surge arrestors and filters in control circuit protect against disturbances. Filtering algorithms and fault tolerant software protect against disturbances and false measurements.
Power Connections	Supply phase, neutral and earth. Load phase, neutral and earth.
Surge Protection	Heavy duty input and output surge arrestors to protect against extreme surges and lightning on the supply. Dual mode. 4800 joules total.
Displays	Digital display for input voltage, output voltage, input current, output current and frequency. Push button to select display mode.
RFI/EMI Filter	AVR is equipped with RFI/EMI filtering for proper operation of the unit.
Ambient Temperature Range	0 to +55 °C.
Relative Humidity	>95%, non condensing.
Environmental Protection	IP31.
Acoustic Noise	< 45 dB (A).
Expected Service Life	> 25 years.
Standards	Manufactured to comply with :- ISO9001:2000, CE, EN 50081-1:1992, EN 50082-1:1998, EN 55022:1998, EN 61000-4-2:1995/1998, EN 61000-4-3:1996, EN 61000-4-4:1995, EN 61000-4-5:1995, EN 61000-4-6:1996, EN 61000-4-11:1994, DD ENV 50204. 
Dimensions	785 x 460 x 560 (D x W x H) mm.
Weight	82 kg.