▼ Voltright™

FRIDGE-STAB | TV-STAB | A/C-STAB



Voltage stabilisation and protection for televisions, fridges and air conditioners



Voltright™ TV-STAB



Providing you with voltage stabilisation and protection for all your TV and multimedia equipment against high voltage.

The TV-Stab will ensure that high voltage is reduced to safe working level for your TV to operate properly. It will also protect by disconnecting the power when it reaches a very high level.

A built in startup delay will protect against power back surges and prevent frequent switching on and off due to fluctuations.





Practical and useful features

- Microprocessor controlled stabiliser
- Wide input voltage range
- Excellent output voltage stability
- Includes surge and spike suppression
- Incorporates circuit breaker
- Fast response
- Over voltage & under voltage disconnect
- 10 sec startup delay

Features:




















Voltright™ FRIDGE-STAB



Providing you with voltage stabilisation and protection for your domestic fridge/freezer.

The Fridge-Stab will ensure that low voltage and high voltage is brought to safe working level for your fridge to operate properly and cool efficiently. It will also protect by disconnecting the power when it rises to a very high level or drops to a very low level.

A built in startup delay will protect against power back surges and prevent frequent switching on and off due to fluctuations.







Practical and useful features

- Microprocessor controlled stabiliser
- Wide input voltage range
- Excellent output voltage stability
- Includes surge and spike suppression
- Incorporates circuit breaker
- Fast response
- Over voltage & under voltage disconnect
- 3 minute startup delay





Ideal protection for all your refrigeration equipment















Voltright™ A/C-STAB




Providing you with voltage stabilisation and protection for your air conditioner.

The A/C-Stab will ensure that low voltage and high voltage is brought to a safe working level for your A/C to operate properly and to cool efficiently. It will also protect it by disconnecting the power when it rises to a very high level or drops to a very low level.

A built in startup delay will protect against power back surges and prevent frequent switching on and off due to fluctuations.





Practical and useful features

- Microprocessor controlled stabiliser
- Wide input voltage range
- Excellent output voltage stability
- Includes surge and spike suppression
- Incorporates circuit breaker
- Fast response
- Over voltage
- & under voltage disconnect
- 3 minute startup delay



Features:


















FRIDGE-STAB | TV-STAB | A/C-STAB







The Sollatek Stab range - a range of devices that will protect all your valuable equipment

Loaded with features to give you complete

The Sollatek Stab range has some advanced functions:

AVS™ function



The AUTOMATIC VOLTAGE SWITCHER (AVS $^{\mathtt{M}}$) function adds the following protective function: When the

mains power supply fluctuates outside pre-set tolerances (nominally (152V-270V)) the power to your air conditioner is disconnected.

The AVS monitors the voltage for a short period to ensure the power has stabilised before re-connecting. In addition, the start-up delay (3 min) provides protection against power-back surges commonly experienced after resumption of power in a power cut situation.

Surge and spike protection is also incorporated to ensure protection against these events which are very common. They are generated by lightning and nearby switching off and on of other equipment such as vacuum cleaners, pumps, motors, television, elevators etc.

TIMESAVE™ function


TIMESAVE™

TIMESAVE™ adds the following protective function:


The built-in microprocessor adds the advanced feature TimeSave.™ TimeSave™ means that when the mains return to normal, the unit checks the duration of the OFF time. If the unit has been off for more than the standard wait time, then it will reconnect the mains within 10 seconds. This means the Sollatek unit will give you more vital working time than any other stabiliser.

Connectivity


A/C-Stab connectivity



TV-Stab and Fridge-Stab connectivity



TV-Stab and Fridge-Stab socket availability





peace of mind




Specifications

Technical Specifications


Product	TV-Stab 13M	TV-Stab 20M	Fridge-Stab 280M	
Application	Audio-Visual (TV, V	Audio-Visual (TV, Video, Satellite, etc)		
Output Current (A) @45°C	1.3A RMS	2A RMS	1A RMS	
Regulation Range				
Input	120-2	120-290V		
Reconnect Time Delay	10sec	10sec ± 6%		
Spike Protection			140 joules	
Maximum surge current:				
Typical attenuation:				
Protection mode:				
Overload Protection				
TimeSave Function	No	10		
Sockets	2x (6A Indian 3-Pin)	or 1x (EU or UK13A).		
Circuit Breaker				
Cable Length			1m	
Display LEDs				
Weight			1.4Kg	

Fridge-Stab and TV-Stab Dimensions (mm)



	Fridge-Stab 450M	A/C-Stab 120M	A/C-Stab 120L	A/C-Stab 150L		
	Fridge/Freezer (Up to 450L)	Air Conditioner	Air Conditioner	Air Conditioner		
	2A RMS	12A RMS	12A RMS	15A RMS		
	•					
130-290V		164-294V	155-270V			
	31	min ± 6%				
			190 joules			
6.5kA (8/20µs)	·				
50dB @	⊇ 10Mhz					
L-N, L-	-E, N-E		L-N			
Yes	(all)					
		Yes				
1x (6A Indian 3-Pin or EU or UK13A)			Direct			
Input (Res	set breaker)					
			Direct			
LVD/HVD (Re	ed), On (Green)					
			3Kg			

A/C-Stab Dimensions (mm)



Sollatek's **global infrastructure** is delivered through a network with **local presence**



With customers across the world and a local presence in more than 50 countries, Sollatek is able to provide support services wherever you are.

Algeria	Egypt	Jordan	Nigeria	Sweden	USA
Angola	Finland	Kenya	Norway	Sudan	Venezuela
Australia	Ghana	Kazakhstan	Pakistan	Taiwan	Yemen
Azerbijan	Greece	Libya	Philippines	Turkey	Zambia
Benin	Holland	Malawi	Qatar	Tanzania	Zimbabwe
Cameroon	Hong Kong	Mexico	Saudi Arabia	UAE	
Croatia	India	Mozamhique	Sierra Leone	Hoanda	

Sollatek (UK) Ltd

Denmark

Unit 9/10 Newlands Drive, Poyle 14 Industrial Estate, Colnbrook, Slough, Berks SL3 0DX, UK.

Iraq

Tel:

International: +44 1753 688300 National: 01753 688300

Fax:

International: +44 1753 685306 National: 01753 685306

E-mail: sales@sollatek.com **Internet:** www.sollatek.com



Nepal

Sollatek provides you with full back up support and a two year worldwide warranty on all products, with local support in over twenty countries worldwide.

South Africa



www.sollatek.com



United Kingdom

ISO9001: 2008 accredited company

All weights and dimensions are approximate. Specifications are subject to change without prior notice. ©Sollatek (UK) Limited 2013. All Rights Reserved. SOLLATEK and the SOLLATEK device are the trade marks of the Sollatek group of companies.