



Model	SLB18PL	SLB36PL	SLB18SX	SLB26SX
Lamp wattage	18 W	36 W	18 W	26 W
Nominal voltage	12, 24, 48 VDC	12 or 24 VDC	12 or 24 VDC	12 or 24 VDC
Current consumption at 12V	1.3 A	2.5 A	1.5 A	2.3 A
Current consumption at 24V	0.65 A	1.25 A	0.75 A	1.15 A
Current consumption at 48V	0.33 A	N/A	N/A	N/A
Type of tube	Compact Fluorescent	Compact Fluorescent	Sodium SOX-E	Sodium SOX-E
Tube lumen output	1200	2800	1800	3700
Colour of light emitted	White	White	Yellow	Yellow
Inverter frequency (KHz)	>30 KHz	>30 KHz	>30 KHz	>30 KHz
Inverter waveform	Pure sinewave	Pure sinewave	Pure sinewave	Pure sinewave
Inverter efficiency	>90%	>90%	>90%	>90%
Operating temperature range	-10 to +50°C	-10 to +50°C	-10 to +50°C	-10 to +50°C
Open circuit protected	Yes	Yes	Yes	Yes
Short circuit protected	Yes	Yes	Yes	Yes
Reverse polarity protected	Yes	Yes	Yes	Yes
Optional switch	N/A	N/A	N/A	N/A
Warranty period*	Two years	Two years	Two years	Two years
Packaging	Plain carton	Plain carton	Plain carton	Plain carton
Packed dimensions (mm)	420 x 160 x 170	420 x 160 x 170	420 x 160 x 170	420 x 160 x 170
Packed weight (Kg)	2	2	2	2
Order multiple	2	2	2	2
Replacement lamp specifications	Sollatek 68518602	Sollatek 68536802	Sollatek 68518610	Sollatek 68526610
CFLs are 4 pin	Philips 18PLL84 Osram DL1884 GE F18DBX/840 Sylvania L18W/840	Osram DF3684 Sylvania F36W/840 GE F18BX1840	Philips 18SOXE	Philips 26S OXE Osram SXE26 GE SOX26E